



#		Max. Euro-adapter height / Max. Mitchell plate height	Lift range	Arm reach	Length of rear end	Front extensions	Rear extensions	Lift capacity (working load)	Counterweight required for max. lift capacity	Crane & base dolly weight excluding counterweight
V1		424 cm / 13' 11"	420 cm / 13' 9"	336 cm / 11'	279 cm / 9' 2"	1 x 200 cm / 6' 7"	1 x 192 cm / 6' 4"	250 kg / 551 lbs	274 kg / 604 lbs	661 kg / 1457 lbs
V2		502 cm / 16' 5"	576 cm / 18' 11"	434 cm / 14' 3"	279 cm / 9' 2"	1 x 200 cm / 6' 7" + 1 x 100 cm / 3' 3"	1 x 192 cm / 6' 4"	250 kg / 551 lbs	424 kg / 935 lbs	678 kg / 1495 lbs
V3		581 cm / 19' 1"	735 cm / 24' 1"	534 cm / 17' 6"	279 cm / 9' 2"	2 x 200 cm / 6' 7"	1 x 192 cm / 6' 4"	250 kg / 551 lbs	554 kg / 1221 lbs	730 kg / 1610 lbs
V4		659 cm / 21' 7"	891 cm / 29' 3"	632 cm / 20' 9"	279 cm / 9' 2"	2 x 200 cm / 6' 7" + 1 x 100 cm / 3' 3"	1 x 192 cm / 6' 4"	250 kg / 551 lbs	718 kg / 1583 lbs	747 kg / 1648 lbs
V5		738 cm / 24' 3"	1050 cm / 34' 5"	732 cm / 24'	279 cm / 9' 2"	3 x 200 cm / 6' 7"	1 x 192 cm / 6' 4"	250 kg / 551 lbs	896 kg / 1975 lbs	769 kg / 1696 lbs
V6		816 cm / 26' 9"	1205 cm / 39' 6"	830 cm / 27' 3"	279 cm / 9' 2"	3 x 200 cm / 6' 7" + 1 x 100 cm / 3' 3"	1 x 192 cm / 6' 4"	250 kg / 551 lbs	1078 kg / 2377 lbs	802 kg / 1768 lbs
V7		896 cm / 29' 5"	1364 cm / 44' 9"	930 cm / 30' 6"	279 cm / 9' 2"	4 x 200 cm / 6' 7"	1 x 192 cm / 6' 4"	250 kg / 551 lbs	1274 kg / 2809 lbs	841 kg / 1853 lbs
V8		974 cm / 31' 11"	1520 cm / 49' 10"	1028 cm / 33' 9"	279 cm / 9' 2"	4 x 200 cm / 6' 7" + 1 x 100 cm / 3' 3"	1 x 192 cm / 6' 4"	140 kg / 309 lbs	1022 kg / 2253 lbs	835 kg / 1840 lbs
V9		1053 cm / 34' 7"	1679 cm / 55' 1"	1128 cm / 37'	279 cm / 9' 2"	5 x 200 cm / 6' 7"	1 x 192 cm / 6' 4"	140 kg / 309 lbs	1166 kg / 2571 lbs	876 kg / 1931 lbs
V10		1131 cm / 37' 1"	1835 cm / 60' 2"	1225 cm / 40' 2"	279 cm / 9' 2"	5 x 200 cm / 6' 7" + 1 x 100 cm / 3' 3"	1 x 192 cm / 6' 4"	130 kg / 287 lbs	1330 kg / 2932 lbs	893 kg / 1968 lbs
V11		1217 cm / 39' 11"	1955 cm / 64' 2"	1286 cm / 42' 2"	279 cm / 9' 2"	5 x 200 cm / 6' 7" + 1 x 200 cm / 6' 7" conical	1 x 192 cm / 6' 4"	85 kg / 187 lbs	974 kg / 2147 lbs	846 kg / 1865 lbs
V12		1295 cm / 42' 6"	2110 cm / 69' 3"	1384 cm / 45' 5"	279 cm / 9' 2"	5 x 200 cm / 6' 7" + 1 x 100 cm / 3' 3" + 1 x 200 cm / 6' 7" conical	1 x 192 cm / 6' 4"	85 kg / 187 lbs	1134 kg / 2500 lbs	882 kg / 1945 lbs
V13		1374 cm / 45' 1"	2269 cm / 74' 5"	1484 cm / 48' 8"	279 cm / 9' 2"	6 x 200 cm / 6' 7" + 1 x 200 cm / 6' 7" conical	1 x 192 cm / 6' 4"	80 kg / 176 lbs	1218 kg / 2685 lbs	895 kg / 1973 lbs
V14		1452 cm / 47' 8"	2425 cm / 79' 7"	1582 cm / 51' 11"	279 cm / 9' 2"	6 x 200 cm / 6' 7" + 1 x 100 cm / 3' 3" + 1 x 200 cm / 6' 7" conical	1 x 192 cm / 6' 4"	80 kg / 176 lbs	1394 kg / 3073 lbs	915 kg / 2017 lbs
V15		1532 cm / 50' 3"	2584 cm / 84' 9"	1682 cm / 55' 2"	279 cm / 9' 2"	7 x 200 cm / 6' 7" + 1 x 200 cm / 6' 7" conical	1 x 192 cm / 6' 4"	60 kg / 132 lbs	1362 kg / 3003 lbs	927 kg / 2043 lbs

